

CAR★MATE®

TRAILERS INC. ★★☆☆

★ 1982 ★ 25th Anniversary ★ 2007 ★



Contractor Series Dump

Shown with optional tarp kit



6' Wide Low Profile Dump



6' Wide & 7' Wide D.O.W.



5' Wide Dump

www.carmate-trailers.com



Dump Trailers

Some photos include options

CONTRACTOR SERIES DUMP SPECIFICATIONS

SPECIFICATIONS	6.5' WIDE (10K)	6.5' WIDE (12K)	6.5' WIDE (14K)
Overall Width	102"	102"	102"
Dump Bed Side Wall Height	30"	30"	30"
Platform Height	27"	28"	28"
Deck Width	78"	78"	78"
Available Dump Bed Length	12'	12' & 14'	12' & 14'
Volume Capacity	12' - 7.2 Cubic Yards	12' - 7.2 C.Y. / 14' - 8.4 C.Y.	12' - 7.2 C.Y. / 14' - 8.4 C.Y.
Coupler Size, Adjustable	2 5/16" or Lunette Eye	2 5/16" or Lunette Eye	2 5/16" or Lunette Eye
Axle - Slipper Spring	Standard 2 - 6,000#	Standard 2 - 6,000#	Standard 2 - 7,000#
Axle - Dexter Torflex	Optional	Optional	Optional
GVWR	9,990#	12,000#	14,000#
Tires	225/75R15 D Range	235/80R16 E Range	235/80R16 E Range
Wheels	White Spoke - 6 Bolt	White Spoke - 8 Bolt	White Spoke - 8 Bolt
Electric Brakes	Standard	Standard	Standard
Electric Plug	7 Pole	7 Pole	7 Pole
Breakaway Kit w/ Charger	Standard	Standard	Standard
Frame Size	6"	6"	6"
Floor Material	Steel 12 Ga.	Steel 12 Ga.	Steel 12 Ga.
4 - Weld-On "D" Rings	Standard	Standard	Standard
Equipment Ramps	Optional	Optional	Optional
Tarp Kit w/ Straps & Crank	Optional	Optional	Optional
DOT Lighting / LED Sealed	Lifetime Warranty	Lifetime Warranty	Lifetime Warranty
ADDITIONAL STANDARD FEATURES			
Diamond Plate Fenders	7,000# Drop Leg Jack	Conspicuity Striping	Scissor Lift
Double Doors w/ Cam Lock	Monarch Pump w/ 20' Remote	Greaseable Door Hinges	Loading Ramp Brackets
Spring Loaded Tie Backs	12V Deep Cycle Battery	Lockable Steel Tongue Box	Full Length Rub Rail

D.O.W. HYDRAULIC DUMP SPECIFICATIONS

SPECIFICATIONS	6' x 10'	6' x 12'	7' x 12'
Overall Width	75"	75"	84"
Overall Length	14' 6"	16' 6"	16' 6"
Dump Bed Side Wall Height	22"	22"	22"
Platform Height	31"	31"	34"
Deck Width	68"	68"	80"
Dump Bed Length	10'	12'	12'
Coupler Size	2 5/16"	2 5/16"	2 5/16"
Axle	2 - 3500#	2 - 3500#	2 - 6000#
GVWR	7000#	7000#	9990#
Frame Size	2" x 5" Tube	2" x 5" Tube	2" x 6" Tube
Floor Material	Steel 12 Ga.	Steel 12 Ga.	Steel 12 Ga.
Side Walls	Treated Plank or Steel	Treated Plank or Steel	Treated Plank or Steel
Tires	205/75R15 C Range	205/75R15 C Range	225/75R15 D Range
Wheels	White Spoke - 5 Bolt	White Spoke - 5 Bolt	White Spoke - 6 Bolt
Electric Brakes / Both Axles	Standard	Standard	Standard
Electric Plug	7 Pole	7 Pole	7 Pole
Breakaway Kit w/ Charger	Standard	Standard	Standard
Stake Pockets & Rub Rail	Standard	Standard	Standard

LOW PROFILE HYDRAULIC DUMP SPECIFICATIONS

5' WIDE DUMP SPECIFICATIONS

SPECIFICATIONS	6' x 12'	SPECIFICATIONS	
Overall Width	102"	Overall Width	80 3/4"
Overall Length	16' 6"	Overall Length	12' 6"
Dump Bed Side Wall Height	22"	Dump Bed Side Wall Height	18"
Platform Height	29"	Platform Height	24 3/4"
Deck Width	76"	Deck Width	60"
Dump Bed Length	12'	Dump Bed Length	96"
Coupler Size	2 5/16"	Volume Capacity	2.2 Cubic Yards
Axle	2 - 6000#	Coupler Size	2 5/16"
GVWR	9990#	Axle	1 - 5200#
Frame Size	6" Tube	GVWR	5000#
Floor Material	Steel 12 Ga.	Frame Size	4" Tube
Equipment Ramps w/ Tie Downs	Optional	Floor Material	Steel 12 Ga.
Tires	225/75R15 D Range	Tires	225/75R15 D Range
Wheels	White Spoke - 6 Bolt	Wheels	White Spoke - 6 Bolt
Electric Brakes	Standard - Both Axles	Electrical Brakes	Standard
Electric Plug	7 Pole	Electrical Plug	7 Pole
Breakaway Kit w/ Charger	Standard	Breakaway Kit w/ Charger	Standard
Stake Pockets & Rub Rail	Standard		



DEALER IMPRINT